Automatic Scrubbers CT100



26/29 Gallon 28" & 32" Disc / 30" Cylindrical

High Productivity



Large solution tank capacity in minimum external space



Extensive running time (Large battery compartment)



Solution control with automatic stop (Solenoid valve)



Brush control with automatic "delayed" stop



High Performance



SLS (Self Levelling System) automatic main brush pressure control PATENTED



High quality and performance vacuum motor



Exclusive squeegee system assures high performance at low cost



Combined scrubbing-sweeping system that includes debris hopper (R version)







Automatic Scrubbers **CT100**





Ergonomic, User Friendly



Great maneuverability due to optimum weight distribution



Great working visibility



Designed to assure minimum noise levels



Easy to use control panel



Solution tank level indicator



Battery level indicator



Solution tank discharge hose



Recovery tank discharge point and hose at maximum height



Solution tank can be tilted for ease of cleaning



External battery charger plug



On board charger can be easily installed now or later







Automatic Scrubbers **CT100**





Low Maintenance Costs



Inlet and outlet filters for maximum solution tank protection



AFS (Anti Foam System)



Brush replacement without tools



Squeegee blade can be used on 4 sides before replacement



Squeegee assembly and blades replacement without tools



Easy access to internal compartments

Durability



Tanks and surrounding body in high density polyethylene



Oil bath reduction gear box




Brush head designed to absorb harsh impact



Squeegee system designed to absorb harsh impact



Panel control switches protected against water and humidity







Automatic Scrubbers **CT100**







Large tank capacity in minimum external space 26-29 Gallon (100-110 L.) capacity tanks make this model very unique in its category.



Solution control with automatic stop
Saves water and save chemicals. Solution flow stops
and starts upon brush command.



Extensive running timeExtremely large battery compartment allows batteries of up to 5 hours running time.



SLS (Self Leveling System)
Automatic brush pressure control
Constant brush pressure with immediate reaction.
Avoids also excessive brush and actuator wear.



performance at low costIncomparable drying results even on the most difficult surfaces thanks to a very unique design.



Recovery tank can be tiltedEasy to rinse and clean thanks also to smooth internal finishes.

	C1100 B1 70	C1100 B1 85	C1100 B1 75R
Scrubbing Width	28" / 680 mm	32" / 810 mm	30" / 750 mm
Suction Width	40" / 1010 mm	40" / 1010 mm	43" / 1100 mm
Productivity (at max speed)	32940 ft ² /h/ 3060 m ² /h	39230 ft ² /h/ 3645 m ² /h	36330 ft ² /h/ 3375 m ² /h
Number of Brushes	2 (disc)	2 (disc)	2 (cyl)
Solution Tank Size	26 gallon / 100 liter	26 gallon / 100 liter	26 gallon / 100 liter
Recovery Tank Size	29 gallon / 110 liter	29 gallon / 110 liter	29 gallon / 110 liter
Power Supply	24V (4x6V)	24V (4x6V)	24V (4x6V)
Max Speed (traction type)	2.7 mph / 4.5 (electric) Km/h	2.7 mph / 4.5 (electric) Km/h	2.7 mph / 4.5 (electric) Km/h
Weight (net)	374 lbs. / 170 Kg	381 lbs. / 173 Kg	379 lbs. / 172 Kg
Dimensions (LxWxH)	63" x 30" x 43" 1596 mm x 744 mm x 1075 mm	65" x 35" x 43" 1641 mm x 880 mm x 1075 mm	70" x 33" x 43" 1770 mm x 832 mm x 1075 mm



2955 Lone Oak Drive • Eagan, MN 55121 651.686.5399 • Fax 651.686.5695 www.ipceagle.com IPC Eagle Corporation Sales and Service Provided by:

CleanCraft Products, Inc. 800-525-3261 www.cleancraft.com