

FLOOR SCIENCE FINISH

PREMIUM UNIVERSAL SEALER/FINISH PRODUCES A DRAMATIC "WET LOOK" GLOSS ON BOTH RESILIENT AND NON-RESILIENT FLOORS. PROVIDES EXCELLENT DURABILITY AND RESISTANCE TO SCUFFS, SCRATCHES AND BLACK HEEL MARKS. RESPONDS TO CONVENTIONAL, HIGH-SPEED AND ULTRA-HIGH-SPEED MAINTENANCE.

- **Metal crosslinked technology**—synthetic polymeric floor finish creates initial high-gloss without buffing or burnishing. Retains "wet look" with spray buffing or burnishing.
- **Easy to use**—dries in just 30 to 45 minutes. The "built-in" sealer means the finish acts as its own sealer . . . no separate product required. Provides optimum buff response. Features outstanding leveling and adhesion properties.
- **Exceptionally durable**—minimizes the tendency to show scuffs and black heel marks. Repairs easily.
- **Universal applications**—use on vinyl, vinyl composition, vinyl asbestos, asphalt tile and rubber. . . as well as terrazzo, marble, slate, unglazed ceramic and quarry tile, brick and granite.
- **Packaging**—4-1 gallons (U.S.)/3.78 liters per case (code 98391), or 1-5 gallon (U.S.)/18.9 liter "bag-in-a-box" (code 98390).

Distributed by:

CleanCraft Products, Inc.
800-525-3261
www.cleancraft.com



Product No. 2 from the Floor Science™ Floor Care System. It's as simple as ...



FLOOR SCIENCE FINISH

Quite simply, it's brilliant!

HOW TO USE

Floor Science™ FINISH FOR BEST RESULTS:

1. Remove all old finish using Floor Science Stripper (coded #1/red), following label directions.
2. Apply 2 to 3 medium coats of finish using a clean rayon mop. Allow 30 to 45 minutes drying time between coats.
3. Apply additional coats as required until desired gloss is achieved.
4. Buff, spray buff or burnish as desired.

NOTE: Test small areas for adhesion before applying to terrazzo, concrete, new highly polished marble and granite.

To avoid contamination, do not pour unused product back into container.

TECHNICAL DATA:

Non-Volatile
(ASTM LD 2834-72)18.0% min.
pH.....8.8 to 9.2
Recoat30-45 minutes
Weight.....8.57 lbs./gal.
1.03 kg./liter
Freeze/Thaw Stability.....Keep from freezing
Storage Stability (Shelf Life)24 months
Coverage2,000 to 2,500 sq. ft. per
U.S. gallon or 50 to 60
square meters per liter
average, depending on
application rate and
surface porosity



For more information,
call 1-800-242-1677.

For Technical
Assistance, call
1-800-558-2332.

Ask about other quality Drackett Professional products: WINDEX, DRANO, EASY PAKS, VANISH, GLADE, PLEDGE, WHISTLE, TWINKLE, SKIDOO, SURE TRAC, MR. MUSCLE, SANI-SURE AND BEER/CLEAN.



Drackett Professional

Drackett Professional, a Division of ©1994 SC Johnson Wax, Racine, WI 53403



Form No. Z-2F30
Printed in USA